
Local EPC Standard





INTRODUCTION

The Baicells Local EPC solution, or BaiEPC, is for operators who want to run a private network version of the LTE EPC instead of using the Baicells CloudCore EPC. Local EPC provides the essential LTE core network functions:

- Mobility Management Entity (MME)
- Home Subscriber Server (HSS)
- Serving Gateway (SGW)
- Packet Data Network Gateway (PGW)
- Policy & Charging Rules Function (PCRF)

Deploying a BaiEPC gives operators full control of their E2E Baicells network elements, making it possible to customize services or localize deployments for multiple regions. The product is an all-in-one platform which conforms to 3GPP telecommunications standards for efficient network integration.

The Local EPC Standard platform is designed for small to midsized networks, and supports up to 50 eNBs and 5000 subscribers*. Optionally, you can add Layer 2 capabilities for VxLAN and/or GRE tunneling.

The Local EPC Standard server comes with a two-year warranty from the manufacturer. The Local EPC product requires the use of Local OMC+BOSS to manage the network elements and subscribers, which is part of the bundled package. The Local OMC+BOSS product is also sold separately.

*NOTE: For large networks or for customers who require High Availability (using a second server for redundancy and software hot standby), refer to the Local EPC Professional data sheet.

FEATURES

Mobility Management

- Attach/detach/idle
- Paging
- X2, S1 handover
- Tracking area update

Session Management

- Default bearer management
- Dedicated bearer management
- Multiple PDN connections (up to 4 per UE)
- QoS

Networking Functions

- Static and dynamic IP address allocation
- E2E Layer 2 solution (with Baicells UEs)

Policy & Charging

- IMSI/APN based PCC rules
- Offline charging

OAM

- Local management Web GUI
- Northbound APIs for OMC & BOSS

Performance

- Supports up to 50 eNBs
- Supports up to 5000 subscribers

SERVER HARDWARE SPECIFICATIONS

| Туре | LANNER NCA-2510C or similar |
|-----------------|---|
| СРИ | Atom C3758,8C8T 2.2GHz |
| RAM | 16G DDR4 ECC(16*1) |
| Max RAM | 64GB |
| Hard Drive | 2.5" 1T*2 |
| RAID | LSI |
| Rack Size | 1 RU for Local EPC server and 1 RU for Local OMC+BOSS server bundle |
| Ethernet Ports | 4*GbE RRJ45, 4*10G SFP+ |
| Power | 150W AC ATX Single PSU/300W DC ATX Single PSU |
| Throughput | 4 Gbps |
| Weight | ~20 lbs/9 kg (NCA-2510) per server |
| Server Warranty | 2 years |

PART NUMBERS / OPTIONS

| BAICELLS-EPC-L2-BUNDLE | Standard EPC+OMC+L2 (standard license package of 20 eNBs+2000 subs). Initial Commissioning & Support must be purchased. |
|------------------------|---|
| BAICELLS-EPC-BUNDLE | Standard EPC+OMC (standard license package of 20 eNBs+2000 subs). Initial Commissioning & Support must be purchased. |

To order additional licenses, or for information concerning Local EPC Professional or customization, contact sales_na@baicells.com.

Local EPC Standard

